

Spot blaster

Softblasting Systems
by Sodablast

The device that adapts
to your needs!



Extendible
transport handle
Simply move your
material height



Adjustable workload
Simply adjust your workload



Rubber handle
in the front
Perfect grip for easier loading



Nozzle system

Handle with built-in gun holder

Silent rubber blocks for horizontal storage

Two-level handle lock

Beam connection by direct output

Manometer for high accuracy of adjustment

Adjustment of the product flow by progressive screw



KEY POINTS

Tank of 11 liters for a better compromise between autonomy and small size

Components designed for longer life

An even more efficient drain plug for fast and reliable cleaning

Easier handling with two rubber grips

INDICATIONS

Capacity	●●●●●
Polyvalence	●●●●●
Handling	●●●●●
Effectiveness	●●●●●

Softblasting systems
by Sodablast

BECAUSE WE KNOW HOW TO LISTEN TO YOU

TECHNICAL CHARACTERISTICS AND DIMENSIONS

- Tank capacity 11 liter
- Supply pressure 8bar maximum
- Adjustable pressure 0,5 to 8 bar
- Air flow 300 to 1200 liter/min
- Beam..... type gun with M / A control
- Beam length..... 5 meters
- Nozzle type tungsten carbide nozzle*
- Granulate distribution..... progressive screw system
- Filling and emptying..... plug type Guillemin**
- Air connection Express connector / coupler
- Net weight..... 27kg
- Load weight 45kg
- Warranty 3 years manufacturer



We also offer complete turnkey packs with compressor, with a flow rate of 300 to 1200 liters per minute, single-phase electric, three-phase or with heat engine

ETS International UG | Wilhelm Rupert Str.38, 51147-Koln, Germany. Tel. +49 2261 9130865 www.etsint.de

* Diameter determined according to the compressor ** Funnel filling provided